



**SPECIFICATIONS**

1. Current rating: 3A AC, DC
2. Voltage rating: 250V AC, DC
3. Temperature range: -40°C ~ +105°C
4. Insulation resistance: 1000MΩ/ min.
5. Withstanding voltage: 1000V AC/ minute.
6. Contact resistance: 20mΩ/ max.

Material: Phosphor Bronze/Tin plated over nickel  
 Applicable wires: AWG #28~#22  
 Insulation O.D 1.2~1.8mm Max.  
 Suitable KR2501 series housing  
 Q'ty/reel: 9,000PCS



**AsA Electronic Co.**

Tel : (+98) 21 66 73 56 82 Mob : (+98) 912 03 161 02

F					TOLERANCE X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 Angle ±2°	TITLE: XH2.5 Terminal	DRAWN: <i>Arvin 2022.01.13</i>		PART NO.: T25010PT0101F	
							CHECKED:			
		Uniformly arrange the drawings	Shen	2022.01.13			APPROVED:			
MARK	REVISION	DESCRIPTION	SIGNATURE	DATE	UNIT:mm	SCALE:N/A	SHEET:1/1	PROJECTION	VER.:A2	DRAWING NO.:2501T01-F-S

WWW.ASA-ELEC.COM